

Risk Management of concrete road bridges subject to de-icing salts and the possible implications of climate change

- **Gordon Anderson**
- Service Delivery Manager – Highways & Engineering
- Mouchel – Unity Partnership, UK
- gordon.anderson@unitypartnership.com

H Bailey et al
TRL, UK

S Beamish et al
Mouchel, UK

0. CONTENT

1. The need to manage risk
2. Impact of climate change
3. Current monitoring processes
4. Proposed risk management processes
5. Methods of managing risk
6. Reducing rates of corrosion
7. Conclusions

1. INTRODUCTION - The need to manage risk

- In the UK 31.5% of all local authority bridges are of concrete construction
- By deck area, even larger figure of 35.5%
- Reinforcement corrosion is most serious cause of deterioration of concrete bridges
- Primary causes of metallic corrosion – carbonation & chloride ingress
- Leading to cracking, delamination & spalling of concrete

1. INTRODUCTION – The need to manage risk cont.

- Roads & bridges de-icing agent most commonly sodium chloride
- Roads & bridges receive same quantities
- Sodium chloride must when spread go into solution to be effective
 - Below -5 to -7°C solution not formed rapidly
 - Below -15° C not saturated
 - Melting snow & ice can reduce effectiveness
- *Predicted climate change in UK with warmer wetter winters could lead to altered corrosion rates – how do we manage that potential risk?*

2. The effect and / impact of climate change on corrosion rate

- Corrosion processes are complex
 - Materials, geometry, condition & environment
- Two key factors are climate & contaminants
 - Humidity, temperature, contaminants – increased corrosion rates
- Road bridges – a major contaminant is chloride
 - Quantity of de-icer and frequency depends on temperature & precipitation

2. The effect and / impact of climate change on corrosion rate cont.

- Climate has an important effect on corrosion rate
- Average UK temperature is increasing - winters will be warmer and wetter
 - Corrosion acceleration
- Salt will continue to be present
 - May be required less frequently – BUT may be more frequently reapplied

3. Current monitoring processes for concrete road bridges

- Management of Highway structures – A Code of Practice
- All requirements for the management of highways structures
 - All UK highways structures are subject to de-icing salts
- Method comprises a data led approach
 - Leads to analyses, assessments & processes
 - Compilation & maintenance of a database / inventory
 - Development of works programmes

3. Current monitoring processes for concrete road bridges cont.

- Current practice comprises cyclical inspection regimes
 - Routine surveillance, General, Principal, Special and Safety Inspections
- General Inspections – 2 years
 - Calculation of CPI, BCS for the structure, BSCI for the stock
 - BSCI of 100 = 100% potential retained
 - 60 = 40% potential lost
- Principal Inspections – 6 years
 - Direct, close access to structure

4. Proposed risk management processes

- BD 63/07 sets out detailed inspection requirements
 - Risk based approach to planning an inspection regime is allowed BUT seldom used
- No current accepted risk management mechanism
- ***Why should low risk structures require the same inspection regime as higher risk structures?***
- Differing asset owners have varying views
 - HA Interim Advice Note 171/12 provides a systematic approach

4. Proposed risk management processes cont.

- Visual inspection is the core of most inspection regimes
 - Access, traffic management, seasonal restrictions, accuracy, reliability
- TRL has investigated image based GI
 - Benefits of development include:
 - Simplified access
 - complete hi-res image of whole structure
 - remote sharing of images
 - automatic quantifiable data / data interpretation
 - 3-D interactive models

5. Innovative methods of managing risk operationally

- Climate changes - unpredictability / increases in corrosion rates
- Other factors & new technologies
 - Trends demonstrate increasing de-icer use
- Need to reduce chloride use – opposing pressures of need to clear road vs. possible damage to the structure
 - Alternative de-icers
 - Salt is most cost effective / most damaging
 - De-icer often required earlier and more frequently

5. Innovative methods of managing risk operationally cont.

- Drive for innovation and research into de-icers & delivery in UK
 - TRL for Highways Agency, Transport Scotland & National Winter Service Research Group (NWSRG) – new guidance
 - Far lower salt rates in UK at “marginal temperatures”
- Alternative de-icers (below -5 to -7° C) research
 - Alternative or salt mixes – more effective & less salt required
 - Benefits between -7 to 0° C leading to less salt
 - more economy
 - less structural & environmental damage
 - reduced exposure to salt

5. Innovative methods of managing risk operationally cont.

- Other factors to consider:
 - Min spread rates are achieved if optimum time for prevailing conditions is met
 - Forecast temperature, road surface wetness, volume of traffic - wetter the road surface the more de-icer required
 - Traffic helps to effect the salt to dissolve
 - High volume may disperse too quicklyand onto bridge structure
 - Traffic also disperses water - so delay spreading
- Delay to avoid general loss of de-icer , and to allow surface water dispersal – helpful for bridges

6. Reducing rates of corrosion in reinforced concrete bridges

- Need to consider winter service provision at bridge design stage:
 - Ensure components are protected or resistant
 - Detailing to prevent brine seepage
 - Specialised winter provision elements
- Electrochemical means of polarizing the steel reinforcement (-ve)
- Cathodic protection (CP) - suppress / reverse the internally generated corrosion current
- Extensively assessed in UK and elsewhere
- Extensive UK use e.g. Midland Links structures – 100000m² of concrete protected

6. Reducing rates of corrosion in reinforced concrete bridges cont.

- CP can lead to remedial work cost reductions of 20 to 80%
- Sustainable option as is extending the current structure's life – less waste to landfill
- CP performance of 10 – 40 years before maintenance – embedded items with theoretical life of 120 years
- Two main types
 - Impressed Current Cathodic Protection (ICCP) – Long term / large scale / higher budget
 - Sacrificial Anode Cathodic Protection (SACP) – Shorter term / targeted / lower budget

7. CONCLUSIONS – A joined up & targeted approach

- Significant revenue financial pressures in the maintenance of highways infrastructure, including road bridges
- Maximise life of the existing (& new) asset, ensuring whole life cost effectiveness
- Predicted climate changes in the UK – high chance of corrosion rates increasing
- De-icing agents applied in more targeted, optimised ways (from -7°C to 0°C)
- Limit exposure to chlorides – more sustainable
- At design stage new structures include details appropriate to winter service – maybe including active systems

7. CONCLUSIONS – A joined up & targeted approach cont.

- Use of established, effective and sustainable remediation methods such as CP – condition, accessibility, maintenance and available budget
- Systematic risk-based approach to the inspection regimes of bridges - targeted asset management according to need and available budgets
- Manage risk further and reduce costly human intervention by using 2D (maybe 3D) imaging as investigated by TRL
- Use (in UK) of Government / DfT initiatives / resources - Highways Maintenance Efficiency Programme (HMEP) to manage the asset

7. CONCLUSIONS – A joined up & targeted approach cont.

Thank you

Merci

Gracias

Mouchel

G Anderson
P Clapham
S Beamish

gordon.anderson@unitypartnership.com

sam.beamish@mouchel.com

TRL

H Bailey
S Reeves
M Hill
B Cleave
S McRobbie

hbailey@trl.co.uk